

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 44 386 - 07 HH

Company VOSS Fluid GmbH
Postfach 15 40
51679 Wipperfurth, GERMANY

Product Description COMPRESSION COUPLINGS 24°, L-AND S-SERIES, MADE OF STEEL AND STAINLESS STEEL

Type VOSS DKO TAPER COUPLINGS

Environmental Category • None

Technical Data / TECHNICAL DATA

Range of Application

Coupling materials: carbon steel and stainless steel in accordance with DIN 3859-1, table 2 or of higher grades.

Series L (light)		Series S (heavy)	
Pipe O.D. [mm]	Nom. Press. [PN]	Pipe O.D. [mm]	Nom. Press. [PN]
6 - 10	500	6 - 10	800
12 - 18	400	12 - 16	630
22 - 42	250	20 - 38	420

RANGE OF APPLICATION

The aforementioned compression couplings may be used in piping systems of pipe class I to III as well as in non-essential systems under consideration of IACS Req. P2.7, table 8 and GL Rules Chapter 2 - Machinery installation, Section 11.

(continued on page 2)

Test Standard • GL Regulations for the Performance of Type Tests, Chapter 8 and IACS Req. 2001, P2.11 Type Approval of Mechanical Joints (Nov.2001, Rev.1 May 2006).

Documents • Test report no. C101/06 of IMA Dresden • 61070 / 105 to 61070 / 108 issued by WTD 71 • UA.-No.: 4522 issued by Messrs. Voss •
• Technical Documentation

Remarks • None

Valid until 2017-02-20

Page 1 of 2

File No. II.C.05

Hamburg, 2012-03-21

Type Approval Symbol



Germanischer Lloyd

Hanspeter Raschle
Hanspeter Raschle

Peter Gierhan
Peter Gierhan

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 44 386 - 07 HH

TECHNICAL DATA

- The nominal pressure ratings PN represent the max. allowable working pressure inclusive of pressure peaks.
- Pressure ratings, pressure reductions and permissible operating temperatures are to be in accordance with the instructions of the manufacturer.
- The installation of the VOSS DKO taper couplings is to be carried out in accordance with the instructions of the manufacturer and the assembly instructions of DIN 3859-2 as applicable.

Allowable temperature range for VOSS DKO taper couplings and seal materials:

VOSS DKO Stainless Steel	-60 [°C] to 200 [°C]
VOSS DKO Steel	-20 [°C] to 120 [°C]
NBR	-35 [°C] to 100 [°C]
FPM / FKM	-25 [°C] to 200 [°C]

In case of combining VOSS DKO taper couplings with several different types of sealing materials, the highest minimum and the lowest maximum temperature figures are applicable.

- The selection of the VOSS DKO taper couplings for the corresponding application and the right installation are to be in accordance with the instructions of the manufacturer.

Valid until 2017-02-20

Page 2 of 2

File No. II.C.05

Hamburg, 2012-03-21

Type Approval Symbol



Germanischer Lloyd

Hanspeter Raschle
Hanspeter Raschle

Peter Gierhan
Peter Gierhan

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".